

Hydrodynamical Approach to Vehicular Flow in the Urban Street Canyon

Maciej M. Duras

Institute of Physics, Cracow University of Technology, ulica Podchorążych 1, PL-30084
Cracow, Poland

Email: mduras @ riad.usk.pk.edu.pl

AD 2001 March 22

"DCOMP01, The 2001 Annual Meeting of the Division of Computational Physics"; June 25th, 2001 to June 28th, 2001; Massachusetts Institute of Technology, Cambridge, Massachusetts, USA; in: "DCOMP Meeting 2001 Scientific Program DCOMP June 25-28, 2001; Cambridge, Massachusetts"; *Bulletin of the American Physical Society*, Vol. **46**, Part **F**, R1.030 (2001).

Abstract

The vehicular flow in the urban street canyon is considered. The classical field description is used in the modelling of the vehicular movement and of gaseous mixture in generic urban street canyon. The dynamical variables include vehicular densities, velocities, and emissivities: of pollutants, heat and exhaust gases, as well as standard mixture components' variables: densities, velocities, temperature, pressures. The local balances' equations predict the dynamics of the complex system. The automatic control of the vehicular flow is attained by the sets of coordinated traffic lights. The automatic control is aimed at minimization of traffic ecological costs by the application of variational calculus (Lagrange's and Bolz's problems). The theoretical description is accompanied by numerical examples of computer fluid dynamics based on real traffic data.

1 Description of the model.

In the present article we develop a continuum field model of the street canyon. In the next article we will deal with numerical examples [1]. The vehicular flow in the canyon is multilane bidirectional one-level rectilinear, and it is considered with two coordinated signalized junctions [2, 3, 4]. The vehicles belong to different vehicular classes: passenger cars, and trucks. Emissions from the vehicles are based on technical measurements and many types of pollutants are considered (carbon monoxide CO, hydrocarbons HC, nitrogen oxides NO_x). The vehicular dynamics is based on a hydrodynamical approach [5]. The governing equations are the continuity equation for the number of vehicles, and Greenshields' equilibrium speed-density u-k model [6].

The model of dynamics of pollutants is also hydrodynamical. The model consists of a set of mutually interconnected nonlinear, three-dimensional, time-dependent, partial differential

equations with nonzero right-hand sides (sources), and of boundary and of initial problem. The pollutants, oxygen, and the remaining gaseous constituents of air, are treated as mixture of noninteracting, Newtonian, viscous fluid (perfect or ideal gases). The complete model incorporates as variables the following fields: density of the mixture, mass concentrations of constituents of the mixture, velocity of mixture, temperature of mixture, pressure of mixture, intrinsic (internal) energy of mixture, densities of vehicles, and velocities of vehicles. The model is based on the assumption of local laws of balance (conservation) of: mass of the mixture, masses of its constituents, momentum and energy of the mixture, the numbers of the vehicles, as well as of the state equations (Clapeyron's law and Greenshields' model). The equations of dynamics are solved by the finite difference scheme.

The six separate monocriterial optimization problems are formulated by defining the functionals of total travel time, of global emissions of pollutants, and of global concentrations of pollutants, both in the studied street canyon and in its two nearest neighbour substitute canyons. The vector of control is a five-tuple composed of two cycle times, two green times, and one offset time between the traffic lights. The optimal control problem consists of minimization of the six functionals over the admissible control domain.

2 Equations of dynamics.

Under the above model specifications, the complete set of equations of dynamics of the model is formulated as follows (we follow the general idea presented in [7, 8]):

E1. Balance of momentum of mixture - Navier Stokes equation.

$$\rho\left(\frac{\partial \mathbf{v}}{\partial t} + (\mathbf{v} \circ \nabla)\mathbf{v}\right) + S\mathbf{v} = -\nabla p + \eta\Delta\mathbf{v} + \left(\xi + \frac{\eta}{3}\right)\nabla(\text{div}\mathbf{v}) + \mathbf{F}, \quad (1)$$

where η is the first viscosity coefficient ($\eta = 18.1 \cdot 10^{-6} [\frac{\text{kg}}{\text{m}\cdot\text{s}}]$ for air at temperature $T = 293.16$ [K]), ξ is the second viscosity coefficient ($\xi = 15.6 \cdot 10^{-6} [\frac{\text{kg}}{\text{m}\cdot\text{s}}]$ for air at temperature $T = 293.16$ [K]), $\mathbf{F} = \rho\mathbf{g}$ is the gravitational body force density, $\mathbf{g}$ is the gravitational acceleration of Earth ($\mathbf{g} = (0, 0, -9.81) [\frac{\text{m}}{\text{s}^2}]$), $\nabla\mathbf{v}$ is gradient of the vector (so it is a tensor of rank 2). We assume that the gaseous mixture is a compressible and viscous fluid.

E2. Balance of mass of mixture - Equation of continuity.

$$\frac{\partial \rho}{\partial t} + \text{div}(\rho\mathbf{v}) = S. \quad (2)$$

We have assumed the source **D1**.

E3. Balances of masses of constituents of mixture - Diffusion equations.

E3a.

$$\begin{aligned} \rho\left(\frac{\partial c_i}{\partial t} + \mathbf{v} \circ \nabla c_i\right) &= S_i^E - c_i S + \\ &+ \sum_{m=1}^{N-1} \{(D_{im} - D_{iN}) \cdot \text{div}[\rho \nabla(c_m + \frac{k_{T,m}}{T} \nabla T)]\}, i = 1, \dots, N_E. \end{aligned} \quad (3)$$

E3b.

$$\begin{aligned} \rho \left(\frac{\partial c_i}{\partial t} + \mathbf{v} \circ \nabla c_i \right) &= -c_i S + \\ &+ \sum_{m=1}^{N-1} \{ (D_{im} - D_{iN}) \cdot \text{div} [\rho \nabla (c_m + \frac{k_{T,m}}{T} \nabla T)] \}, i = (N_E + 1), \dots, N, \end{aligned} \quad (4)$$

where $D_{im} = D_{mi}$ is the mutual diffusivity coefficient from the i -th constituent to m -th one, and D_{ii} is the autodiffusivity coefficient of the i -th constituent, and $k_{T,m}$ is the thermodiffusion ratio of the m -th constituent. The diffusivity coefficients and thermodiffusion ratios are constant and known). In **E3a** we have assumed the sources **D1-D2**. In **E3b** only the source **D1** is taken into account. Since the mixture is in motion, we cannot neglect the convection term: $\mathbf{v} \circ \nabla c_i$. We assume that the barodiffusion and gravitodiffusion coefficients are equal to zero.

E4. Balance of energy of mixture.

$$\rho \left(\frac{\partial \epsilon}{\partial t} + \mathbf{v} \circ \nabla \epsilon \right) = - \left(-\frac{1}{2} \mathbf{v}^2 + \epsilon \right) S + \mathbf{T} : \nabla \mathbf{v} + \text{div}(-\mathbf{q}) + \sigma, \quad (5)$$

where ϵ is the mass density of intrinsic (internal) energy of the air mixture, $\mathbf{T}$ is the stress tensor, symbol $:$ denotes the contraction operation, $\mathbf{q}$ is the vector of flux of heat. We assume that [2]:

$$\epsilon = \sum_{i=1}^N \epsilon_i, \quad (6)$$

$$\begin{aligned} \epsilon_i &= \frac{1}{m_i} \{ c_i k_B T \exp(-\frac{m_i |\mathbf{g}| z}{k_B T}) \cdot [(-\frac{z}{c}) \cdot (1 - \exp(-\frac{m_i |\mathbf{g}| c}{k_B T})) - \exp(-\frac{m_i |\mathbf{g}| c}{k_B T})] \} + \\ &+ \tilde{\mu}_i c_i, \end{aligned} \quad (7)$$

$$\tilde{\mu}_i = \frac{\mu_i}{m_i}, \quad (8)$$

$$\mu_i = k_B T \cdot \{ \ln[(c_i p)(k_B T)^{-\frac{c_{p,i}}{k_B}} (\frac{m_{\text{air}}}{m_i}) (\frac{2\pi h^2}{m_i})^{\frac{3}{2}}] \} + m_i |\mathbf{g}| z, \quad (9)$$

$$\begin{aligned} T_{mk} &= -p \delta_{mk} + \\ &+ \eta \cdot [(\frac{\partial v_m}{\partial x_k} + \frac{\partial v_k}{\partial x_m} - \frac{2}{3} \delta_{mk} \text{div}(\mathbf{v})) \frac{\partial v_k}{\partial x_m}] + \xi \cdot [(\delta_{mk} \text{div}(\mathbf{v}))^2], m, k = 1, \dots, 3, \end{aligned} \quad (10)$$

$$\mathbf{T} : \nabla \mathbf{v} = \sum_{m=1}^3 \sum_{k=1}^3 T_{mk} \frac{\partial v_m}{\partial x_k}, \quad (11)$$

$$\mathbf{q} = \sum_{i=1}^N \{ [(\frac{\beta_i T}{\alpha_{ii}} + \tilde{\mu}_i) \mathbf{j}_i] + [(-\kappa) \nabla T] \}, \quad (12)$$

$$\mathbf{j}_i = -\rho D_{ii} (c_i + \frac{k_{T,i}}{T} \nabla T), \quad (13)$$

$$\alpha_{ii} = \frac{[\rho D_{ii}]}{[(\frac{\partial \tilde{\mu}_i}{\partial c_i})_{(c_n)_{n=1, \dots, N, i \neq n, T, p}}]}, \quad (14)$$

$$\beta_i = [\rho D_{ii}] \cdot \left\{ \frac{k_{T,i}}{T} - \frac{[(\frac{\partial \bar{\mu}_i}{\partial T})(c_n)_{n=1,\dots,N,p}]}{[(\frac{\partial \bar{\mu}_i}{\partial c_i})(c_n)_{n=1,\dots,N,i \neq n,T,p}]} \right\}, \quad (15)$$

where ϵ_i is the mass density of intrinsic (internal) energy of the i th constituent of the air mixture, m_i the molecular mass of the i th constituent, $k_B = 1.3807 \cdot 10^{-23} [\frac{J}{kg}]$ is Boltzmann's constant, μ_i is the complete partial chemical potential of the i th constituent of the air mixture (it is complete since it is composed of chemical potential without external force field and of external potential), $m_{\text{air}} = 28.966 \text{ [u]}$ is the molecular mass of air ($1 \text{ [u]} = 1.66054 \cdot 10^{-27} \text{ [kg]}$), δ_{mk} is Kronecker's delta, $c_{p,i}$ is the specific heat at constant pressure of the i th constituent of air mixture, $h = 6.62608 \cdot 10^{-34} [J \cdot s]$ is Planck's constant, $\mathbf{j}_i$ is the vector of flux of mass of the i th constituent of the air mixture, and κ is the coefficient of thermal conductivity of air. These magnitudes are derived from Grand Canonical ensemble with external gravitational Newtonian field.

E5. Equation of state of the mixture - Constitutive equation - Clapeyron's equation.

$$\frac{p}{\rho} = \frac{R}{m_{\text{air}}} \cdot T \quad (16)$$

is Clapeyron's equation of state for a gaseous mixture, where $R = 8.3145 [\frac{J}{\text{mole} \cdot K}]$ is the gas constant.

$$p_i = c_i \cdot \frac{m_{\text{air}}}{m_i} \cdot p \quad (17)$$

are partial pressures of constituents according to Dalton's law.

E6. Balances of numbers of vehicles - Equations of continuity of vehicles.

$$\frac{\partial k_{l,vt}^s}{\partial t} + \text{div}(k_{l,vt}^s \mathbf{w}_{l,vt}^s) = 0. \quad (18)$$

E7. Equations of state of vehicles - Greenshields model.

$$\mathbf{w}_{l,vt}^s(x, t) = (w_{l,vt,f}^s \cdot (1 - \frac{k_{l,vt}^s(x, t)}{k_{l,vt,jam}^s}), 0, 0). \quad (19)$$

The Greenshields equilibrium speed-density u-k model is assumed [6]. The values of maximum free flow speed $w_{l,vt,f}^s$, and of jam vehicular densities $k_{l,vt,jam}^s$, are given in Tables 3 and 8 of [1].

E8. Technical parameters.

The dependence of emissivity on the density and velocity of vehicles is assumed in the form:

E8a.

$$e_{l,ct,vt}^s(x, t) = k_{l,vt}^s(x, t) \cdot [(\frac{|\mathbf{w}_{l,vt}^s(x, t)| - \tilde{w}_{ct,vt,i_l}}{\tilde{w}_{ct,vt,i_l+1} - \tilde{w}_{ct,vt,i_l}}) \cdot (\tilde{e}_{ct,vt,i_l+1} - \tilde{e}_{ct,vt,i_l}) + \tilde{e}_{ct,vt,i_l}], \quad (20)$$

where $\tilde{w}_{ct,vt,i_l}$ are experimental velocities, $|\mathbf{w}_{l,vt}^s(x,t)| \in (\tilde{w}_{ct,vt,i_l}, \tilde{w}_{ct,vt,i_l+1})$, $\tilde{e}_{ct,vt,i_l}$, are experimental emissions of the *ctth* exhaust gas from single vehicle of *vtth* type at velocities $\tilde{w}_{ct,vt,i_l}$, respectively, measured in $[\frac{\text{kg}}{\text{veh}\cdot\text{s}}]$, $i_l = 1, \dots, N_{EM}$, N_{EM} is the number of experimental measurements. Similarly, the dependence of the change of the linear density of energy on the density and velocity of vehicles is taken in the form:

E8b.

$$\sigma_{l,vt}^s(x,t) = q_{vt} \cdot k_{l,vt}^s(x,t) \cdot \left[\left(\frac{|\mathbf{w}_{l,vt}^s(x,t)| - \bar{w}_{vt,i_l}}{\bar{w}_{vt,i_l+1} - \bar{w}_{vt,i_l}} \right) \cdot (\sigma_{vt,i_l+1} - \sigma_{vt,i_l}) + \sigma_{vt,i_l} \right], \quad (21)$$

where σ_{vt,i_l} , are experimental values of consumption of gasoline/diesel for a single vehicle of *vtth* type at velocities $\bar{w}_{vt,i_l}$, respectively, measured in $[\frac{\text{kg}}{\text{veh}\cdot\text{s}}]$, q_{vt} is the emitted combustion energy per unit mass of gasoline/diesel $[\frac{\text{J}}{\text{kg}}]$.

3 Optimization problems.

Our control task is the minimization of the measures of the total travel time (TTT) [5], emissions (E), and concentrations (C) of exhaust gases in the street canyon, therefore the appropriate optimization problems may be formulated as follows [2]:

F0. Vector of control.

$$\mathbf{u} = (g_1, C_1, g_2, C_2, F) \in U^{\text{adm}}, \quad (1)$$

where $\mathbf{u}$ is vector of boundary control, g_m are green times, C_m are cycle times, F is offset time, and U^{adm} is a set of admissible control variables (compare **A8**, **A9**, **B5**, **B5S**, **B5SS**).

We define six functionals **F1-F6** of the total travel time, emissions, and concentrations of pollutants in single canyon, and in canyon with the nearest neighbour substitute canyons, respectively.

F1. Total travel time for a single canyon.

$$J_{\text{TTT}}(\mathbf{u}) = \sum_{s=1}^2 \sum_{l=1}^{n_s} \sum_{vt=1}^{VT} \int_0^a \int_0^{T_S} k_{l,vt}^s(x,t) dx dt. \quad (2)$$

F2. Global emission for a single canyon.

$$J_{\text{E}}(\mathbf{u}) = \sum_{s=1}^2 \sum_{l=1}^{n_s} \sum_{ct=1}^{CT} \sum_{vt=1}^{VT} \int_0^a \int_0^{T_S} e_{l,ct,vt}^s(x,t) dx dt. \quad (3)$$

F3. Global pollutants concentration for a single canyon.

$$J_{\text{C}}(\mathbf{u}) = \rho_{\text{STP}} \cdot \sum_{i=1}^{N_E-1} \int_0^a \int_0^b \int_0^c \int_0^{T_S} c_i(x,y,z,t) dx dy dz dt. \quad (4)$$

F4. Total travel time for the canyon in street subnetwork.

$$J_{\text{TTT},\text{ext}}(\mathbf{u}) = J_{\text{TTT}}(\mathbf{u}) + \quad (5)$$

$$+ a \cdot \sum_{s=1}^2 \alpha_{\text{TTT},\text{ext}}^s \sum_{l=1}^{n_s} \sum_{vt=1}^{VT} k_{l,vt,\text{jam}}^s \cdot (C_s - g_s).$$

F5. Global emission for the canyon in street subnetwork.

$$J_{\text{E},\text{ext}}(\mathbf{u}) = J_{\text{E}}(\mathbf{u}) + \quad (6)$$

$$+ a \cdot \sum_{s=1}^2 \alpha_{\text{E},\text{ext}}^s \sum_{l=1}^{n_s} \sum_{ct=1}^{CT} \sum_{vt=1}^{VT} e_{l,ct,vt,\text{jam}}^s \cdot (C_s - g_s).$$

F6. Global pollutants concentration for the canyon in street subnetwork.

$$J_{\text{C},\text{ext}}(\mathbf{u}) = J_{\text{C}}(\mathbf{u}) + \quad (7)$$

$$+ \rho_{\text{STP}} \cdot a \cdot b \cdot c \cdot \sum_{i=1}^{N_E-1} c_{i,\text{STP}} \cdot \sum_{s=1}^2 \alpha_{\text{C},\text{ext}}^s \cdot (C_s - g_s).$$

The integrands $k_{l,vt}^s, e_{l,ct,vt}^s, c_i$ in functionals **F1-F6** depend on the control vector $\mathbf{u}$ **F0** through the boundary conditions **B0-B8**, through the equations of dynamics **E1-E8**, as well as, through the sources **D0-D2**. The value of the vector of control u directly affects the boundary conditions **B5, B5S, B5SS**, and then the boundary conditions **B6-B8** for vehicular densities, velocities, and emissivities. It also affects the sources **D0-D2**. Next, it propagates to the equations of dynamics **E1-E8** and then it influences the values of functionals **F1-F6**. We only deal with six monocriterial optimization problems **O1-O6**, and not with one multicriterial problem. We put the scaling parameters equal to unity: $\alpha_{\text{TTT},\text{ext}}^s = \alpha_{\text{E},\text{ext}}^s = \alpha_{\text{C},\text{ext}}^s = 1.0$, in functionals **F4-F6**. ρ_{STP} is the density of air at standard temperature and pressure STP, $c_{i,\text{STP}}$ is concentration of the i th constituent of air at standard temperature and pressure. J_{TTT} and $J_{\text{TTT},\text{ext}}$ are measured in $[\text{veh} \cdot \text{s}]$, J_{E} and $J_{\text{E},\text{ext}}$ are measured in $[\text{kg}]$, and J_{C} and $J_{\text{C},\text{ext}}$ are measured in $[\text{kg} \cdot \text{s}]$, respectively.

Now we formulate six separate monocriterial optimization problems **O1-O6** that consist in minimization of functionals **F1-F6** with respect to control vector **F0** over admissible domain, while the equations of dynamics **E1-E8** are fulfilled.

O1. Minimization of total travel time for a single canyon.

$$J_{\text{TTT}}^* = J_{\text{TTT}}(\mathbf{u}_{\text{TTT}}^*) = \min\{\mathbf{u} \in U^{\text{adm}} : J_{\text{TTT}}(\mathbf{u})\}; \quad (8)$$

O2. Minimization of global emission for a single canyon.

$$J_{\text{E}}^* = J_{\text{E}}(\mathbf{u}_{\text{E}}^*) = \min\{\mathbf{u} \in U^{\text{adm}} : J_{\text{E}}(\mathbf{u})\}; \quad (9)$$

O3. Minimization of global pollutants concentration for a single canyon.

$$J_{\text{C}}^* = J_{\text{C}}(\mathbf{u}_{\text{C}}^*) = \min\{\mathbf{u} \in U^{\text{adm}} : J_{\text{C}}(\mathbf{u})\}; \quad (10)$$

O4. Minimization of total travel time for a canyon in street subnetwork.

$$J_{\text{TTT},\text{ext}}^* = J_{\text{TTT},\text{ext}}(\mathbf{u}_{\text{TTT},\text{ext}}^*) = \min\{\mathbf{u} \in U^{\text{adm}} : J_{\text{TTT},\text{ext}}(\mathbf{u})\}; \quad (11)$$

O5. Minimization of global emission for a canyon in street subnetwork.

$$J_{\text{E},\text{ext}}^* = J_{\text{E},\text{ext}}(\mathbf{u}_{\text{E},\text{ext}}^*) = \min\{\mathbf{u} \in U^{\text{adm}} : J_{\text{E},\text{ext}}(\mathbf{u})\}; \quad (12)$$

O6. Minimization of global pollutants concentration for a canyon in street subnetwork.

$$J_{\text{C},\text{ext}}^* = J_{\text{C},\text{ext}}(\mathbf{u}_{\text{C},\text{ext}}^*) = \min\{\mathbf{u} \in U^{\text{adm}} : J_{\text{C},\text{ext}}(\mathbf{u})\}, \quad (13)$$

where J_{TTT}^* , J_{E}^* , J_{C}^* , $J_{\text{TTT},\text{ext}}^*$, $J_{\text{E},\text{ext}}^*$, $J_{\text{C},\text{ext}}^*$, are the minimal values of the functionals **F1-F6**, and $\mathbf{u}_{\text{TTT}}^*$, $\mathbf{u}_{\text{E}}^*$, $\mathbf{u}_{\text{C}}^*$, $\mathbf{u}_{\text{TTT},\text{ext}}^*$, $\mathbf{u}_{\text{E},\text{ext}}^*$, $\mathbf{u}_{\text{C},\text{ext}}^*$, are control vectors at which the functionals reach the minima, respectively.

4 Conclusions.

The proecological traffic control idea and advanced model of the street canyon have been developed. It has been found that the proposed model represents the main features of complex air pollution phenomena.

References

- [1] M. M. DURAS, Continuum Field Model of Street Canyon: Numerical Examples, Engineering Transactions, 1999, submitted.
- [2] M. M. DURAS, Road Traffic Control in Street Canyons, Ph. D. Thesis, University of Mining and Metallurgy, Cracow, August 1998, pp. 1-363, 1998.
- [3] A. ADAMSKI, and M. M. DURAS, Environmental Traffic Control Issues in Street Canyons, Polish Journal of Environmental Studies, **6**, 1, 13-20, 1997.
- [4] A. ADAMSKI, and M. M. DURAS, Air Pollution Optimal Traffic Control Issues in Integrated Street, Polish Journal of Environmental Studies, **8**, 1, 7-17, 1999.
- [5] P. G. MICHALOPOULOS, D. E. BESKOS, and J.-K. LIN, Analysis of Interrupted Traffic Flow by Finite Difference Methods, Transportation Research-B, **18B**, 4/5, 409-421, 1984.
- [6] B. D. GREENSHIELDS, A study of traffic capacity, Proceedings of Highway Research Board, **14**, pp. 448-477, 1934.
- [7] A. CEMAL ERINGEN, and G. A. MAUGIN, Electrodynamics of Continua, Springer-Verlag, New York, 1990 Vol. I, Chapters 3, 5; Vol. II, Chapters 9, 10.

- [8] L. D. LANDAU, and E. M. LIFSHITZ, Theoretical Physics: Hydrodynamics, Nauka, Moscow, 1986, Chapters 2, 6 [in Russian].
- [9] M. M. DURAS, Continuum Field Model of Street Canyon: Theoretical Description, Engineering Transactions, **48**, 4, 2000.
- [10] M. BRZEŹAŃSKI, Evaluation of Transport Emission of the Amount on a Chosen Section of the Road Network in Cracow, KONMOT'98, Table 2, 1998 [in Polish].